

GRAVOPLY® 1



- Interior signage
- Identification plates
- Key tags

- Satin finish for Gravoply 1
- Engraving depth .012" (0.3 mm)
- 2-ply or 3-ply
- Many colors and thicknesses
- Abrasion resistant

Specifications

Surface	Satin
Profile engraving depth	.012" (0.3 mm)
Full sheet	24" x 48" (610 mm x 1220 mm)
Half sheet	24" x 24" (610 mm x 610 mm)
Quarter sheet	12" x 24" (305 mm x 610 mm)
Composition	XT/ABS

Capabilities

Interior	■		Exterior
Shear	■	■	Saw
Silk screen	■	■	Hot stamp
Scratch resistant	■	■	Flexible
Break resistant	■		UV resistant
Min. temp.		200°F/93°C	Max. temp.

DID YOU KNOW?

We can match any Gravoply cap with any Gravoply core. See page 15 for more details.



	Surface color	Core color	2-ply			3-ply	
			0.8 mm 1/32"	1.6 mm 1/16"	2.4 mm 3/32"	1.6 mm 1/16"	3.2 mm 1/8"
●	white	red		17385	17484		29699
●	white	burgundy		29576			
●	white	azure blue		17396	17489		
●	white	black	17263	17331	22030	29578	29700
●	white	navy blue	31258				
●	almond	black		32293			
●	red	white	17267	17506	17472	29580	29702
●	red	black		17454			
●	burgundy	white		17463			
●	yellow	azure blue		17373			
●	yellow	red	31600				
●	yellow	black	17273	17366	17478	29579	17525
●	pine green	white		17410	17495		
●	navy blue	white	29525	29581			29706
●	azure blue	white	17270	17353	17475	29603	29705
●	chocolate brown	white		31641	31645		29704
●	silver gray	white		29584			
●	silver gray	burgundy		29587			
●	silver gray	azure blue		32157			
●	silver gray	black		17379			
●	black	white	17250	17319	17467	29604	17521
●	black	red		29601			
●	white	magenta		29573			
●	white	apple green		17313			
●	white	pine green		29561			
●	white	teal		29568			
●	white	brown		29575			
●	new york white	burgundy		29570			
●	new york white	brown		29571			
●	ivory	chocolate brown		17310			
●	almond	burgundy		29562			
●	almond	silver gray		32284			
●	rust	white		17448			
●	passion pink	white		45953			
●	pink	white		30384			
●	pink	magenta		29577			

GRAVOPLY® 1



- Interior signage
- Identification plates

- Satin finish
- Engraving depth .012" (0.3 mm)
- 2-ply or 3-ply
- Many colors and thicknesses
- Durable .012" (0.3 mm) cap layer



Specifications

Surface	Satin
Profile engraving depth	.012" (0.3 mm)
Full sheet	24" x 48" (610 mm x 1220 mm)
Half sheet	24" x 24" (610 mm x 610 mm)
Quarter sheet	12" x 24" (305 mm x 610 mm)
Composition	XT/ABS

Capabilities

Interior	■		Exterior
Shear	■	■	Saw
Silk screen	■	■	Hot stamp
Scratch resistant	■	■	Flexible
Break resistant	■		UV resistant
Min. temp.		200°F/93°C	Max. temp.

DID YOU KNOW?

Any cap/core combinations can be custom manufactured to be 3-ply. See page 15 for more details.

Surface color	Core color	2-ply			3-ply	
		0.8 mm 1/32"	1.6 mm 1/16"	2.4 mm 3/32"	1.6 mm 1/16"	3.2 mm 1/8"
● red	yellow		17445			
● burgundy	silver grey		17431			
● orange	white		17407	17492		
● orange	black		17404			
● burnt orange	black	29560	29566			
● yellow	white		29564			
● yellow	magenta		29565			
● teal	white		29569			
● maui blue	white		45901			
● pine green	almond		29574			
● green	white		17393			
● grass	white		45892			
● apple green	white	17292	17442	17503	29602	
● navy blue	silver gray		29582			
● blue metallic	white		17363			
● azure blue	yellow		17439			
● air force blue	white		17428	17500		
● purple	white		17436			
● cocoa	white		17419			
● cocoa	chocolate brown		17413			
● brown	white		17388			29703
● silver gray	almond		29586			
● silver gray	navy		29585			
● light gray	black		29583	17379		
● metallic gray	white		17376			
● black	yellow		17399			
● black	silver gray		29572			
● light walnut	white		29598			
● american walnut	white		29599			29707
● glossy walnut	white		29600			

Gravoply® .020" (0.5 mm) & .040" (1.0 mm)

.020 is a very flexible version of Gravoply is most often used for window signs & pipe and plaque messaging.

Surface color	Core color	2-ply	3-ply
		0.5 mm .020"	1.0 mm .040"
● white	black/white		31233
● black	white	31238	
● black	white/black		31250

GRAVOPLY® 1 DESIGN



- Interior signage
- Identification plates

- Textured or matte finishes
- Textured finish provides extreme scratch resistance
- Matte finish offers a glare-free presentation

Textured Specifications

Surface	Textured
Engraving depth	.012" (0.3 mm)
Full sheet	24" x 48" (610 mm x 1220 mm)
Half sheet	24" x 24" (610 mm x 610 mm)
Quarter sheet	12" x 24" (305 mm x 610 mm)
Composition	XT/ABS

Decor Specifications

Surface	Matte
Engraving depth	.012" (0.3 mm)
Full sheet	24" x 48" (610 mm x 1220 mm)
Half sheet	24" x 24" (610 mm x 610 mm)
Quarter sheet	12" x 24" (305 mm x 610 mm)
Composition	ABS

Capabilities

Interior	■		Exterior
Shear	■	■	Saw
Silk screen	■	■	Hot stamp
Scratch resistant	■	■	Flexible
Break resistant	■		UV resistant
Min. temp.		200°F/93°C	Max. temp.

DID YOU KNOW?

Don't see the finish color combination you want? We can produce any color combination in any finish. See page 15 for details.

Gravoply® 1 Textured

			2-ply	
			1.6 mm	
			1/16"	
	Surface color	Core color		
●	white	black	29605	
●	white	red	29606	
●	white	blue	29607	
●	yellow	black	29609	
●	black	white	29610	
●	passion pink	white	45954	
●	red	white	29611	
●	azure blue	white	29612	
●	apple green	white	29613	
●	grass	white	45893	
●	maui blue	white	45950	



Gravoply® Matte Decor

			2-ply	
			1.6 mm	
			1/16"	
	Surface color	Core color		
●	new york white	slate	29614	
●	evergreen	candlewick	32744	
●	candlewick	evergreen	32743	
●	candlewick	slate	29616	
●	slate	new york white	29617	

*Gravoply® Translucent (satin finish)

			2-ply			3-ply	
			0.8 mm	1.6 mm	2.4 mm	1.6 mm	3.2 mm
			1/32"	1/16"	3/32"	1/16"	1/8"
	Surface color	Core color					
●	black	translucent white	17295				
●	black	translucent red	17298				
●	red	translucent white	17301				
●	white	translucent red	29618				

*Excellent for backlit signs