

GRAVOPLY® 2



- Badges
- Identification plates
- Interior signage



Bold items are valued priced!

- Microthin surface layer
- Perfect for small characters and detailed logos
- Low glare matte finish
- 2-ply and 3-ply

Specifications

Surface	Matte
Profile engraving depth	.002" (0.1 mm)
Full sheet	24" x 48" (610 mm x 1220 mm)
Half sheet	24" x 24" (610 mm x 610 mm)
Quarter sheet	12" x 24" (305 mm x 610 mm)
Composition	ABS

Capabilities

Interior	■		Exterior
Shear	■	■	Saw
Silk screen	■	■	Hot stamp
Scratch resistant	■	■	Flexible
Break resistant	■		UV resistant
Min. temp.		200°F/93°C	Max. temp.

DID YOU KNOW?

We can custom manufacture your badges and all you have to do is engrave. See page 12.

	Surface color	Core color	2-ply		3-ply	
			0.8 mm	1.6 mm	3.2 mm	1.6 mm
●	white	red		21928		
●	white	azure blue		21908		
●	white	black	21850	21919		
●	red	white	21851	21921	22016	31697
●	yellow	red		21913		
●	yellow	black		21936		31528
●	azure blue	white	31401	21923		31402
●	black	white	21849	21917	29732	31253
●	white	burgundy		21874		
●	almond	burgundy		29709		
●	red	yellow		21910		
●	burgundy	white		21932		
●	yellow	blue		21896		
●	apple green	white		21905		
●	pine green	white		21938		
●	pine green	yellow		21916		
●	sky blue	white		21934		
●	sky blue	black		21895		
●	azure blue	yellow		21911		
●	royal blue	white		21907		
●	brown	white		21930		
●	chocolate brown	white		21876	31647	31644
●	gray	white		21927		
●	gray	black		21915		
●	black	yellow		21940		

GRAVOPLY® 2



- Badges
- Identification plates
- Interior signage



The ultimate in scratch and wear resistance!

- Gravoply 2 Gloss has an extra durable scratch resistant glossy cap
- Microthin surface layer
- Perfect for small characters and detailed logos
- Low glare matte finish on woods, granites and tech patterns

Gravoply® 2

	Surface color	Core color	2-ply	
			1.6 mm	1/16"
●	white	black	23977	
●	white	red	23981	
●	yellow	black	23982	
●	red	white	23978	
●	emerald green	white	23983	
●	blue	white	23979	
●	grey	white	23980	
●	black	white	23976	

Gravoply® 2 Woods

	Surface color	Core color	2-ply	
			1.6 mm	3.2 mm
			1/16"	1/8"
●	satın light walnut	white	21885	
●	satın american walnut	white		29707
●	matte american walnut	white	21880	
●	satın colonial walnut	white	21879	

Specifications

Surface	Matte
Profile engraving depth	.002" (0.1 mm)
Full sheet	24" x 48" (610 mm x 1220 mm)
Half sheet	24" x 24" (610 mm x 610 mm)
Quarter sheet	12" x 24" (305 mm x 610 mm)
Composition	ABS

Gravoply® 2 Naturals

	Surface color	Core color	2-ply	
			1.6 mm	1/16"
●	green marble	almond	22026	

Gravoply® 2 Tech Patterns

	Surface color	Core color	2-ply	
			1.6 mm	1/16"
●	black pinstripe	white	22019	
●	silver grid	black	22022	

Capabilities

Interior	■		Exterior
Shear	■	■	Saw
Silk screen	■	■	Hot stamp
Scratch resistant	■	■	Flexible
Break resistant	■		UV resistant
Min. temp.		200°F/93°C	Max. temp.



Within the continental US call +1.800.843.7637

Outside the continental US call +1.770.623.0331