



# GRAVOSTRAT<sup>®</sup> Phenolic



## Industrial identification

- Phenolic material
- Low glare finish
- 3-ply
- Resistant to chemicals and solvents
- Non-flammable
- Conforms to USA military specifications ASTM D 709 ES-1, ES-2, ES-3, L-P-387
- Electrically non-conductive and abrasion resistant
- Saw cut
- Interior use
- Adhesive okay on quarter sheets only
- Bevel - yes

## Low glare

	Surface color	Core color	3-ply	
			1.6 mm 1/16"	3.2 mm 1/8"
●	white	black	30635	30636
●	fire red	white	31117	31119
●	black	white	30647	30648
●	yellow	black	30755	30756

\* Additional colors available. Call for more information.

## Specifications

Surface	Low glare
Profile engraving depth	.012" (0.3 mm)
Full sheet	36" x 48" (914 mm x 1220 mm)
Half sheet	18" x 48" (457 mm x 1220 mm)
Half sheet	36" x 24" (914 mm x 610 mm)
Quarter sheet	18" x 24" (457 mm x 610 mm)
Composition	Rigid thermoset material

## Capabilities

Interior	Exterior
Shear	Saw
Silk screen	Hot stamp
Scratch resistant	Flexible
Break resistant	UV resistant
Min. temp.	30°F/0°C
	200°F/93°C
	Max. temp.

Note: 18" x 48" (457mm x 1220mm) or smaller ships UPS. 36" x 48" (914 mm x 1220 mm) ships via truck.

This material can be engraved but not cut by a laser.

Within the continental US call +1.800.843.7637

Outside the continental US call +1.770.623.0331